



Female – Femmina – Muffe – Femelle :

| Size Base BG Taille | Thread Filetto Anschluss Filetage | Part Number Codice Articolo Artikelnummer Désignation | A                                | B          | D         | P         | X         | Weight Peso Gewicht Poids | Package Confezione Packungseinheit Colis |
|---------------------|-----------------------------------|---|----------------------------------|------------|-----------|-----------|-----------|---------------------------|--|
| mm                  | inch.                             |   | mm (in)                          | mm (in)    | mm (in)   | mm (in)   | mm (in)   | g (lbs)                   | No.                                      |
| 3.2                 | 1/8"                              | FFH02 18GAS F   | 1/8" BSP Female                  | 46 (1.81)  | 20 (0.79) |           | 18 (0.71) |                           |  |
| 6.3                 | 1/4"                              | FFH04 14GAS F   | 1/4" BSP Female                  | 59 (2.32)  | 27 (1.06) |           | 24 (0.94) |                           |  |
| 6.3                 | 1/4"                              | FFH04 14NPT F   | 1/4" NPTF Female                 | 59 (2.32)  | 27 (1.06) |           | 24 (0.94) |                           |  |
| 10                  | 3/8"                              | FFH06 38GAS F   | 3/8" BSP Female                  | 75 (2.95)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06 12GAS F   | 1/2" BSP Female                  | 79 (3.11)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06 38NPT F   | 3/8" NPTF Female                 | 75 (2.95)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06 12NPT F   | 1/2" NPTF Female                 | 78 (3.07)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06 12SAE F   | 3/4" UNF Female ORB              | 79 (3.11)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06-2/1815 F  | M18x1,5 Male 12L                 | 75 (2.95)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06-2/2215 F  | M22x1,5 Male 15L                 | 87 (3.43)  | 30 (1.18) |           | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06-7/1815 F  | M18x1,5 Male Bulkhead Short 12L  | 101 (3.98) | 30 (1.18) | 26 (1.02) | 27 (1.06) |                           |  |
| 10                  | 3/8"                              | FFH06-7/2215 F  | M22x1,5 Male Bulkhead Short 15L  | 98 (3.86)  | 30 (1.18) | 26 (1.02) | 27 (1.06) |                           |  |
| 12.5                | 1/2"                              | FFH08 12GAS F   | 1/2" BSP Female                  | 81 (3.19)  | 38 (1.50) |           | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08 34GAS F   | 3/4" BSP Female                  | 85 (3.35)  | 38 (1.50) |           | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08 12NPT F   | 1/2" NPTF Female                 | 81 (3.19)  | 38 (1.50) |           | 32 (1.26) |                           |  |
| 12.5                | 1/2"                              | FFH08 34NPT F   | 3/4" NPTF Female                 | 81 (3.19)  | 38 (1.50) |           | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08 12SAE F   | 3/4" UNF Female ORB              | 81 (3.19)  | 38 (1.50) |           | 32 (1.26) |                           |  |
| 12.5                | 1/2"                              | FFH08 58SAE F   | 7/8" UNF Female ORB              | 81 (3.19)  | 38 (1.50) |           | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08 34SAE F   | 1-1/16" UN Female ORB            | 87 (3.43)  | 38 (1.50) |           | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08-12/58S F  | 1" UNS Male Bulkhead ORFS        | 112 (4.41) | 38 (1.50) | 38 (1.50) | 32 (1.26) |                           |  |
| 12.5                | 1/2"                              | FFH08-12/34S F  | 1-3/16" UN Male Bulkhead ORFS    | 113 (4.45) | 38 (1.50) | 39 (1.54) | 36 (1.42) |                           |  |
| 12.5                | 1/2"                              | FFH08-14/58S F  | 7/8" - 14 UNF 2A Male Bulkhead   | 111 (4.37) | 38 (1.50) | 42 (1.65) | 34 (1.34) |                           |  |
| 12.5                | 1/2"                              | FFH08-14/34S F  | 1-1/16" - 12 UN 2A Male Bulkhead | 116 (4.57) | 38 (1.50) | 45 (1.77) | 34 (1.34) |                           |  |
| 16                  | 5/8"                              | FFH10 34GAS F   | 3/4" BSP Female                  | 92 (3.62)  | 42 (1.65) |           | 38 (1.50) |                           |  |
| 16                  | 5/8"                              | FFH10 34SAE F   | 1-1/16" UN Female ORB            | 95 (3.74)  | 42 (1.65) |           | 38 (1.50) |                           |  |
| 19                  | 3/4"                              | FFH12 34GAS F   | 3/4" BSP Female                  | 100 (3.94) | 48 (1.89) |           | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12 1GAS F  | 1" BSP Female                    | 104 (4.09) | 48 (1.89) |           | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12 34NPT F   | 3/4" NPTF Female                 | 100 (3.94) | 48 (1.89) |           | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12 34SAE F   | 1-1/16" UN Female ORB            | 104 (4.09) | 48 (1.89) |           | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12 1SAE F  | 1-5/16" UN Female ORB            | 104 (4.09) | 48 (1.89) |           | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12-12/34S F  | 1-3/16" UN Male Bulkhead ORFS    | 133 (5.24) | 48 (1.89) | 41 (1.61) | 42 (1.65) |                           |  |
| 19                  | 3/4"                              | FFH12-14/34S F  | 1-1/16" - 12 UN 2A Male Bulkhead | 136 (5.35) | 48 (1.89) | 44 (1.73) | 42 (1.65) |                           |  |
| 25                  | 1"                                | FFH16 1GAS F  | 1" BSP Female                    | 100 (3.94) | 55 (2.17) |           | 50 (1.97) |                           |  |
| 25                  | 1"                                | FFH16 1NPT F  | 1" NPT Female                    | 100 (3.94) | 55 (2.17) |           | 50 (1.97) |                           |  |
| 25                  | 1"                                | FFH16 1SAE F  | 1-5/16" UN Female ORB            | 100 (3.94) | 55 (2.17) |           | 50 (1.97) |                           |  |
| 25                  | 1"                                | FFH16 114GAS F  | 1-1/4" BSP Female                | 103 (4.06) | 55 (2.17) |           | 50 (1.97) |                           |  |

Male

Size Base Taille

mm

3.2

6.3

6.3

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

10

## Accessories - Accessori - Zubehör - Accessoires

| Size<br>Base<br>BG<br>Taille |       | Dust protections<br>Tappi Protezione<br>Staubschutzteile<br>Capuchons |                                      |  | Dust protections<br>Tappi Protezione<br>Staubschutzteile<br>Capuchons |  |  | Seal Kits<br>Guarnizioni di ricambio<br>Ersatzdichtungen<br>Joints | Package<br>Confezione<br>Packungseinheit<br>Colis |
|------------------------------|-------|---|--------------------------------------|--|---|--|--|--|---|
|                              |       |   |                                      |  |   |  |  |  |   |
|                              |       | PVC   | Aluminum                             | PVC  | Aluminum  |  |  |  |   |
| mm                           | inch. | Part Number<br>Codice Articolo<br>Artikelnummer<br>Désignation        | Colour<br>Colore<br>Farbe<br>Couleur | Part Number<br>Codice Articolo<br>Artikelnummer<br>Désignation | Colour<br>Colore<br>Farbe<br>Couleur                                  | Part Number<br>Codice Articolo<br>Artikelnummer<br>Désignation | Part Number<br>Codice Articolo<br>Artikelnummer<br>Désignation |  |   |
| 3,2                          | 1/8"  |   |                                      |  |   |  |  | SK FFH02   | 1*  |
| 6.3                          | 1/4"  | TM 2FI14  | ●                                    | TM 2FI14 S   | TF 2FI14  | ●  | TF 2FI14 S   | SK MF 14   | 1**   |
| 10                           | 3/8"  | TMF 38  | ●                                    | TM 2FN38 S   | TFF 38  | ●  | TF 2FN38 S   | SK FFH06   | 1**   |
| 12.5                         | 1/2"  | TM 2FI12  | ●                                    | TM 2FI12 S   | TF 2FI12  | ●  | TF 2FI12 S   | SK FFH08   | 1***  |
| 16                           | 5/8"  | TM 2FI58  | ●                                    |  | TF 2FI58  | ●  |  | SK FFH10   | 1***  |
| 19                           | 3/4"  | TM 2FI34  | ●                                    | TM 2FI34 S   | TF 2FI34  | ●  | TF 2FI34 S   | SK FFH12   | 1***  |
| 25                           | 1"    | TM 2FI1   | ●                                    | TM 2FI1 S  | TM 2FI1   | ●  | TF 2FI1 S  | SK FFH16   | 1***  |

\* - 10 NBR & PTFE seals    \*\* - 10 Polyurethane seals    \*\*\* - 10 Polyurethane & PTFE seals

For pressures > 35 MPa (5075 PSI) use NPT thread  
 Usare z'letto NPT per pressioni > 35 MPa (5075 PSI)  
 NPT Gewinde für > 35 MPa (5075 PSI) benutzen  
 Pour les pressions > 35 MPa (5075 PSI) utiliser le z'letage NPT

### Thread Filetto Anschluss Filetage

